



4/9/2014

ENTERED

DEPARTMENT OF THE AIR FORCE
27TH SPECIAL OPERATIONS MISSION SUPPORT GROUP (AFSOC)
CANNON AIR FORCE BASE NEW MEXICO

Lt Col Anthony S. Figiera
Commander, 27 SOCES
506 Air Commando Way
Cannon AFB NM 88103-5003

MAY 2 2014

Hazardous Waste Bureau

Mr. John Kieling, Chief
Hazardous Waste Bureau
New Mexico Environment Department
2905 Rodeo Park Drive East Bldg 1
Santa Fe NM 87505-6063

Dear Mr. Kieling

Attached is the "*SWMU 127 Risk Screening Evaluation*". If you have any questions regarding this submittal, please contact Mr. Ron Lancaster, Chief, Installation Management Flight at (575) 784-1146.

Sincerely


ANTHONY S. FIGIERA, Lt Col, USAF

Attachment:

1. SWMU 127 Risk Screening Evaluation

cc:

Mr. Daniel Comeau NMED

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
95476	1.52E+04	o-Xylene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.70E-02	1.00E-05	5.18E-03	25	8,661	417.60	630.30	3.63E+02	1.78E+02	0.0E+00	1.0E-01	L

END

INTERMEDIATE CALCULATIONS SHEET

Source- building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor- wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	1.52E+04	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack- to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,404	2.04E-03	8.79E-02	1.75E-04	4.52E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	7.26E-01	1.48E+06	0.10	1.26E+00	4.52E-03	4.00E+02	1.05E+03	7.42E-05	1.10E+02

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
NA	1.0E-01

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.60E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	7.5E-01

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

Soil Properties Lookup Table										
SCS Soil Type	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	Bulk Density (g/cm ³)	θ_w (cm ³ /cm ³)	SCS Soil Name
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc} (cm ² /g)	Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Pure component water solubility, S (mg/L)	Henry's law constant H' (unitless)	Henry's law constant at reference temperature, H (atm·m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RFC (mg/m ³)	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
95476	1.52E+04	o-Xylene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.70E-02	1.00E-05	5.18E-03	25	8,661	417.60	630.30	3.63E+02	1.78E+02	0.0E+00	1.0E-01	L

END

INTERMEDIATE CALCULATIONS SHEET

Source- building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor- wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	1.52E+04	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack- to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,404	2.04E-03	8.79E-02	1.75E-04	4.52E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	7.26E-01	1.48E+06	0.10	1.26E+00	4.52E-03	4.00E+02	1.05E+03	7.42E-05	1.10E+02

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
NA	1.0E-01

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.60E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	1.1E+00

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
95476	6.78E+03	o-Xylene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.70E-02	1.00E-05	5.18E-03	25	8,661	417.60	630.30	3.63E+02	1.78E+02	0.0E+00	1.0E-01	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	6.78E+03	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,404	2.04E-03	8.79E-02	1.75E-04	4.52E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	7.26E-01	6.63E+05	0.10	1.26E+00	4.52E-03	4.00E+02	1.05E+03	7.42E-05	4.92E+01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
NA	1.0E-01

NA	1.0E-01
----	---------

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.60E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	4.7E-01

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
108883	4.65E+03	Toluene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.70E-02	8.60E-06	6.62E-03	25	7,930	383.78	591.79	1.82E+02	5.26E+02	0.0E+00	5.0E+00	L

END

INTERMEDIATE CALCULATIONS SHEET

Source- building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor- wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	4.65E+03	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack- to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	9,154	2.92E-03	1.26E-01	1.75E-04	4.52E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	3.64E-01	1.07E+06	0.10	1.26E+00	4.52E-03	4.00E+02	1.05E+03	7.42E-05	7.96E+01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
NA	5.0E+00

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	2.86E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	1.1E-02

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RfC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
108883	4.65E+03	Toluene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.70E-02	8.60E-06	6.62E-03	25	7,930	383.78	591.79	1.82E+02	5.26E+02	0.0E+00	5.0E+00	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	4.65E+03	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	9,154	2.92E-03	1.26E-01	1.75E-04	4.52E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	3.64E-01	1.07E+06	0.10	1.26E+00	4.52E-03	4.00E+02	1.05E+03	7.42E-05	7.96E+01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
NA	5.0E+00

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	2.86E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	1.5E-02

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
127184	2.90E+00	Tetrachloroethylene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	549	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
534	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	2.90E+00	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	9,553	7.81E-03	3.36E-01	1.75E-04	3.74E-03	534

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	3.10E-01	1.84E+03	0.10	1.26E+00	3.74E-03	4.00E+02	4.49E+03	6.29E-05	1.15E-01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.06E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
7.3E-09	2.0E-03

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
127184	2.90E+00	Tetrachloroethylene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	549	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm ³ /cm ³)	Vadose zone effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Vadose zone soil intrinsic permeability, k_i (cm ²)	Vadose zone soil relative air permeability, k_{rg} (cm ²)	Vadose zone soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (µg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
534	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	2.90E+00	1.69E+04

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm·m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm·s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	9,553	7.81E-03	3.36E-01	1.75E-04	3.74E-03	534

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (µg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m ³)
15	3.10E-01	1.84E+03	0.10	1.26E+00	3.74E-03	4.00E+02	4.49E+03	6.29E-05	1.15E-01

Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.06E+05	NA

MESSAGE SUMMARY BELOW:

END

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
1.2E-08	2.8E-03

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
100414	1.25E+03	Ethylbenzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.50E-02	7.80E-06	7.86E-03	25	8,501	409.34	617.20	3.63E+02	1.69E+02	2.5E-06	1.0E+00	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm ³ /cm ³)	Vadose zone effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Vadose zone soil intrinsic permeability, k_i (cm ²)	Vadose zone soil relative air permeability, k_{rg} (cm ²)	Vadose zone soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (µg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	1.25E+03	1.69E+04

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm·m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm·s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,155	3.17E-03	1.36E-01	1.75E-04	3.89E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (µg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m ³)
15	7.26E-01	1.88E+05	0.10	1.26E+00	3.89E-03	4.00E+02	3.20E+03	7.42E-05	1.39E+01

Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
2.5E-06	1.0E+00

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.54E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
8.5E-06	9.5E-03

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
100414	1.25E+03	Ethylbenzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.50E-02	7.80E-06	7.86E-03	25	8,501	409.34	617.20	3.63E+02	1.69E+02	2.5E-06	1.0E+00	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	1.25E+03	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,155	3.17E-03	1.36E-01	1.75E-04	3.89E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	7.26E-01	1.88E+05	0.10	1.26E+00	3.89E-03	4.00E+02	3.20E+03	7.42E-05	1.39E+01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
2.5E-06	1.0E+00

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.54E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
1.4E-05	1.3E-02

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

Soil Properties Lookup Table										
SCS Soil Type	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	Bulk Density (g/cm ³)	θ_w (cm ³ /cm ³)	SCS Soil Name
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc} (cm ² /g)	Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Pure component water solubility, S (mg/L)	Henry's law constant H' (unitless)	Henry's law constant at reference temperature, H (atm·m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RFC (mg/m ³)	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
100414	1.20E+03	Ethylbenzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.50E-02	7.80E-06	7.86E-03	25	8,501	409.34	617.20	3.63E+02	1.69E+02	2.5E-06	1.0E+00	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	1.20E+03	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	10,155	3.17E-03	1.36E-01	1.75E-04	3.89E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	7.26E-01	1.80E+05	0.10	1.26E+00	3.89E-03	4.00E+02	3.20E+03	7.42E-05	1.34E+01

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
2.5E-06	1.0E+00

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	1.54E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
1.4E-05	1.3E-02

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
71432	2.81E+02	Benzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.80E-02	9.80E-06	5.54E-03	25	7,342	353.24	562.16	5.89E+01	1.79E+03	7.8E-06	3.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Source- building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor- wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	2.81E+02	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack- to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	8,122	2.68E-03	1.15E-01	1.75E-04	4.57E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	1.18E-01	1.09E+05	0.10	1.26E+00	4.57E-03	4.00E+02	9.71E+02	7.42E-05	8.11E+00

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
7.8E-06	3.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	5.31E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
1.5E-05	1.9E-01

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
71432	2.81E+02	Benzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.80E-02	9.80E-06	5.54E-03	25	7,342	353.24	562.16	5.89E+01	1.79E+03	7.8E-06	3.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^v (cm ³ /cm ³)	Vadose zone effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Vadose zone soil intrinsic permeability, k_i (cm ²)	Vadose zone soil relative air permeability, k_{rg} (cm ²)	Vadose zone soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (µg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	2.81E+02	1.69E+04

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm·m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm·s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	8,122	2.68E-03	1.15E-01	1.75E-04	4.57E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (µg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m ³)
15	1.18E-01	1.09E+05	0.10	1.26E+00	4.57E-03	4.00E+02	9.71E+02	7.42E-05	8.11E+00

Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
7.8E-06	3.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	5.31E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
2.6E-05	2.6E-01

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

SCS Soil Type	Soil Properties Lookup Table							Bulk Density		SCS Soil Name
	K_s (cm/h)	α_1 (1/cm)	N (unitless)	M (unitless)	n (cm ³ /cm ³)	θ_t (cm ³ /cm ³)	Mean Grain Diameter (cm)	(g/cm ³)	θ_w (cm ³ /cm ³)	
C	0.61	0.01496	1.253	0.2019	0.459	0.098	0.0092	1.43	0.215	Clay
CL	0.34	0.01581	1.416	0.2938	0.442	0.079	0.016	1.48	0.168	Clay Loam
L	0.50	0.01112	1.472	0.3207	0.399	0.061	0.020	1.59	0.148	Loam
LS	4.38	0.03475	1.746	0.4273	0.390	0.049	0.040	1.62	0.076	Loamy Sand
S	26.78	0.03524	3.177	0.6852	0.375	0.053	0.044	1.66	0.054	Sand
SC	0.47	0.03342	1.208	0.1722	0.385	0.117	0.025	1.63	0.197	Sandy Clay
SCL	0.55	0.02109	1.330	0.2481	0.384	0.063	0.029	1.63	0.146	Sandy Clay Loam
SI	1.82	0.00658	1.679	0.4044	0.489	0.050	0.0046	1.35	0.167	Silt
SIC	0.40	0.01622	1.321	0.2430	0.481	0.111	0.0039	1.38	0.216	Silty Clay
SICL	0.46	0.00839	1.521	0.3425	0.482	0.090	0.0056	1.37	0.198	Silty Clay Loam
SIL	0.76	0.00506	1.663	0.3987	0.439	0.065	0.011	1.49	0.180	Silt Loam
SL	1.60	0.02667	1.449	0.3099	0.387	0.039	0.030	1.62	0.103	Sandy Loam

Chemical Properties Lookup Table																
CAS No.	Chemical	Organic carbon partition coefficient, K_{oc}	Diffusivity in air, D_a	Diffusivity in water, D_w	Pure component water solubility, S	Henry's law constant H'	Henry's law constant at reference temperature, H	Henry's law constant reference temperature, T_R	Normal boiling point, T_B	Critical temperature, T_C	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$	Unit risk factor, URF	Reference conc., RFC	Physical state at soil temperature, (S,L,G)	URF extrapolated (X)	RfC extrapolated (X)
		(cm ² /g)	(cm ² /s)	(cm ² /s)	(mg/L)	(unitless)	(atm·m ³ /mol)	(°C)	(°K)	(°K)	(cal/mol)	(µg/m ³) ⁻¹	(mg/m ³)			
630206	1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044	MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976	Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

DATA ENTRY SHEET

SL-SCREEN
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

Reset to Defaults

ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Initial soil conc., C_R ($\mu\text{g}/\text{kg}$)	Chemical
71432	8.70E+01	Benzene

MORE
↓

ENTER Depth below grade to bottom of enclosed space floor, L_F (15 or 200 cm)	ENTER Depth below grade to top of contamination, L_t (cm)	ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k_v (cm^2)
15	15	10	SIC		

MORE
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Vadose zone soil total porosity, n^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_w^V (cm^3/cm^3)	ENTER Vadose zone soil organic carbon fraction, f_{oc}^V (unitless)	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) Q_{soil} (L/m)
SIC	1.38	0.481	0.216	0.002	

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-05	1

END

Used to calculate risk-based
soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3)^{-1}$)	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
8.80E-02	9.80E-06	5.54E-03	25	7,342	353.24	562.16	5.89E+01	1.79E+03	7.8E-06	3.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Source-building separation, L_T (cm)	Vadose zone soil air-filled porosity, θ_a^V (cm^3/cm^3)	Vadose zone effective total fluid saturation, S_{ie} (cm^3/cm^3)	Vadose zone soil intrinsic permeability, k_i (cm^2)	Vadose zone soil relative air permeability, k_{rg} (cm^2)	Vadose zone soil effective vapor permeability, k_v (cm^2)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R ($\mu\text{g}/\text{kg}$)	Bldg. ventilation rate, $Q_{building}$ (cm^3/s)
1	0.265	0.284	1.48E-09	0.844	1.25E-09	4,000	8.70E+01	1.69E+04

Area of enclosed space below grade, A_B (cm^2)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Vadose zone effective diffusion coefficient, D_v^{eff} (cm^2/s)	Diffusion path length, L_d (cm)
1.00E+06	4.00E-04	15	8,122	2.68E-03	1.15E-01	1.75E-04	4.57E-03	1

Convection path length, L_p (cm)	Soil-water partition coefficient, K_d (cm^3/g)	Source vapor conc., C_{source} ($\mu\text{g}/\text{m}^3$)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm^3/s)	Crack effective diffusion coefficient, D^{crack} (cm^2/s)	Area of crack, A_{crack} (cm^2)	Exponent of equivalent foundation Peclet number, $\exp(Pe)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ ($\mu\text{g}/\text{m}^3$)
15	1.18E-01	3.38E+04	0.10	1.26E+00	4.57E-03	4.00E+02	9.71E+02	7.42E-05	2.51E+00

Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
7.8E-06	3.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	5.31E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
8.0E-06	8.0E-02

MESSAGE SUMMARY BELOW:

END

VLOOKUP TABLES

95578 2-Chlorophenol	3.88E+02	5.01E-02	9.46E-06	2.20E+04	1.60E-02	3.90E-04	25	447.53	675.00	9.572	0.0E+00	1.8E-02	L		X
95636 1,2,4-Trimethylbenzene	1.35E+03	6.06E-02	7.92E-06	5.70E+01	2.52E-01	6.14E-03	25	442.30	649.17	9.369	0.0E+00	6.0E-03	L		
96184 1,2,3-Trichloropropane	2.20E+01	7.10E-02	7.90E-06	1.75E+03	1.67E-02	4.08E-04	25	430.00	652.00	9.171	5.7E-04	4.9E-03	L	X	
96333 Methyl acrylate	4.53E+00	9.76E-02	1.02E-05	6.00E+04	7.68E-03	1.87E-04	25	353.70	536.00	7.749	0.0E+00	1.1E-01	L		X
97632 Ethylmethacrylate	2.95E+01	6.53E-02	8.37E-06	3.67E+03	3.44E-02	8.40E-04	25	390.00	571.00	10.957	0.0E+00	3.2E-01	L		X
98066 tert-Butylbenzene	7.71E+02	5.65E-02	8.02E-06	2.95E+01	4.87E-01	1.19E-02	25	442.10	1220.00	8.980	0.0E+00	1.4E-01	L		X
98828 Cumene	4.89E+02	6.50E-02	7.10E-06	6.13E+01	4.74E+01	1.46E-02	25	425.56	631.10	10.335	0.0E+00	4.0E-01	L		
98862 Acetophenone	5.77E+01	6.00E-02	8.73E-06	6.13E+03	4.38E-04	1.07E-05	25	475.00	709.50	11.732	0.0E+00	3.5E-01	S,L		X
98953 Nitrobenzene	6.46E+01	7.60E-02	8.60E-06	2.09E+03	9.82E-04	2.39E-05	25	483.95	719.00	10.566	0.0E+00	2.0E-03	L		
100414 Ethylbenzene	3.63E+02	7.50E-02	7.80E-06	1.69E+02	3.22E-01	7.86E-03	25	409.34	617.20	8.501	0.0E+00	1.0E+00	L		
100425 Styrene	7.76E+02	7.10E-02	8.00E-06	3.10E+02	1.12E-01	2.74E-03	25	418.31	636.00	8.737	0.0E+00	1.0E+00	L		
100447 Benzylchloride	6.14E+01	7.50E-02	7.80E-06	5.25E+02	1.70E-02	4.14E-04	25	452.00	685.00	8.773	4.9E-05	0.0E+00	L	X	
100527 Benzaldehyde	4.59E+01	7.21E-02	9.07E-06	3.30E+03	9.73E-04	2.37E-05	25	452.00	695.00	11.658	0.0E+00	3.5E-01	L		X
103651 n-Propylbenzene	5.62E+02	6.01E-02	7.83E-06	6.00E+01	4.37E-01	1.07E-02	25	432.20	630.00	9.123	0.0E+00	1.4E-01	L		X
104518 n-Butylbenzene	1.11E+03	5.70E-02	8.12E-06	2.00E+00	5.38E-01	1.31E-02	25	456.46	660.50	9.290	0.0E+00	1.4E-01	L		X
106423 p-Xylene	3.89E+02	7.69E-02	8.44E-06	1.85E+02	3.13E-01	7.64E-03	25	411.52	616.20	8.250	0.0E+00	1.0E-01	L		
106467 1,4-Dichlorobenzene	6.17E+02	6.90E-02	7.90E-06	7.90E+01	9.82E-02	2.39E-03	25	447.21	684.75	9.271	0.0E+00	8.0E-01	S		
106934 1,2-Dibromoethane (ethylene dib	2.50E+01	2.17E-02	1.19E-05	4.18E+03	3.04E-02	7.41E-04	25	404.60	583.00	8.310	2.2E-04	2.0E-04	L		
106990 1,3-Butadiene	1.91E+01	2.49E-01	1.08E-05	7.35E+02	3.01E+00	7.34E-02	25	268.60	425.00	5.370	3.0E-02	2.0E-03	L		
107028 Acrolein	2.76E+00	1.05E-01	1.22E-05	2.13E+05	4.99E-03	1.22E-04	25	325.60	506.00	6.731	0.0E+00	2.0E-05	L		
107062 1,2-Dichloroethane	1.74E+01	1.04E-01	9.90E-06	8.52E+03	4.00E-02	9.77E-04	25	356.65	561.00	7.643	2.6E-05	0.0E+00	L		
107131 Acrylonitrile	5.90E+00	1.22E-01	1.34E-05	7.40E+04	4.21E-03	1.03E-04	25	350.30	519.00	7.786	6.8E-05	2.0E-03	L		
108054 Vinyl acetate	5.25E+00	8.50E-02	9.20E-06	2.00E+04	2.09E-02	5.10E-04	25	345.65	519.13	7.800	0.0E+00	2.0E-01	L		
108101 Methylisobutylketone (4-methyl-2	9.06E+00	7.50E-02	7.80E-06	1.90E+04	5.64E-03	1.38E-04	25	389.50	571.00	8.243	0.0E+00	3.0E+00	L		
108383 m-Xylene	4.07E+02	7.00E-02	7.80E-06	1.61E+02	3.00E-01	7.32E-03	25	412.27	617.05	8.523	0.0E+00	1.0E-01	L		
108678 1,3,5-Trimethylbenzene	1.35E+03	6.02E-02	8.67E-06	2.00E+00	2.41E-01	5.87E-03	25	437.89	637.25	9.321	0.0E+00	6.0E-03	L		
108872 Methylcyclohexane	7.85E+01	7.35E-02	8.52E-06	1.40E+01	4.22E+00	1.03E-01	25	373.90	572.20	7.474	0.0E+00	3.0E+00	L		
108883 Toluene	1.82E+02	8.70E-02	8.60E-06	5.26E+02	2.72E-01	6.62E-03	25	383.78	591.79	7.930	0.0E+00	4.0E-01	L		
108907 Chlorobenzene	2.19E+02	7.30E-02	8.70E-06	4.72E+02	1.51E-01	3.69E-03	25	404.87	632.40	8.410	0.0E+00	6.0E-02	L		
109693 1-Chlorobutane	1.72E+01	8.26E-02	1.00E-05	1.10E+03	6.93E-01	1.69E-02	25	351.60	542.00	7.263	0.0E+00	1.4E+00	L		X
110009 Furan	1.86E+01	1.04E-01	1.22E-05	1.00E+04	2.21E-01	5.39E-03	25	304.60	490.20	6.477	0.0E+00	3.5E-03	L		X
110543 Hexane	4.34E+01	2.00E-01	7.77E-06	1.24E+01	6.82E+01	1.66E+00	25	341.70	508.00	6.895	0.0E+00	2.0E-01	L		
111444 Bis(2-chloroethyl)ether	1.55E+01	6.92E-02	7.53E-06	1.72E+04	7.36E-04	1.80E-05	25	451.15	659.79	10.803	3.3E-04	0.0E+00	L		
115297 Endosulfan	2.14E+03	1.15E-02	4.55E-06	5.10E-01	4.58E-04	1.12E-05	25	674.43	942.94	14.000	0.0E+00	2.1E-02	S		X
118741 Hexachlorobenzene	5.50E+04	5.42E-02	5.91E-06	5.00E-03	5.40E-02	1.32E-03	25	582.55	825.00	14.447	4.6E-04	2.8E-03	S		X
120821 1,2,4-Trichlorobenzene	1.78E+03	3.00E-02	8.23E-06	4.88E+01	5.81E-02	1.42E-03	25	486.15	725.00	10.471	0.0E+00	4.0E-03	L		
123739 Crotonaldehyde (2-butenal)	4.82E+00	9.56E-02	1.07E-05	3.69E+04	7.99E-04	1.95E-05	25	375.20	568.00	9	5.4E-04	0.0E+00	L	X	
124481 Chlorodibromomethane	6.31E+01	1.96E-02	1.05E-05	2.60E+03	3.20E-02	7.81E-04	25	416.14	678.20	5.900	2.4E-05	7.0E-02	L	X	X
126987 Methacrylonitrile	3.58E+01	1.12E-01	1.32E-05	2.54E+04	1.01E-02	2.46E-04	25	363.30	554.00	7.600	0.0E+00	7.0E-04	L		
126998 2-Chloro-1,3-butadiene (chloropr	6.73E+01	8.58E-02	1.03E-05	2.12E+03	4.91E-01	1.20E-02	25	332.40	525.00	8.075	0.0E+00	7.0E-03	L		
127184 Tetrachloroethylene	1.55E+02	7.20E-02	8.20E-06	2.00E+02	7.53E-01	1.84E-02	25	394.40	620.20	8.288	5.9E-06	6.0E-01	L		
129000 Pyrene	1.05E+05	2.72E-02	7.24E-06	1.35E+00	4.50E-04	1.10E-05	25	667.95	936	14370	0.0E+00	1.1E-01	S		X
132649 Dibenzofuran	5.15E+03	2.38E-02	6.00E-06	3.10E+00	5.15E-04	1.26E-05	25	560	824	66400	0.0E+00	1.4E-02	S		X
135988 sec-Butylbenzene	9.66E+02	5.70E-02	8.12E-06	3.94E+00	5.68E-01	1.39E-02	25	446.5	679	88730	0.0E+00	1.4E-01	L		X
141786 Ethylacetate	6.44E+00	7.32E-02	9.70E-06	8.03E+04	5.64E-03	1.38E-04	25	350.26	523.3	7633.66	0.0E+00	3.2E+00	L		X
156592 cis-1,2-Dichloroethylene	3.55E+01	7.36E-02	1.13E-05	3.50E+03	1.67E-01	4.07E-03	25	333.65	544	7192	0.0E+00	3.5E-02	L		X
156605 trans-1,2-Dichloroethylene	5.25E+01	7.07E-02	1.19E-05	6.30E+03	3.84E-01	9.36E-03	25	320.85	516.5	6717	0.0E+00	7.0E-02	L		X
205992 Benzo(b)fluoranthene	1.23E+06	2.26E-02	5.56E-06	1.50E-03	4.54E-03	1.11E-04	25	715.9	969.27	17000	2.1E-04	0.0E+00	S	X	
218019 Chrysene	3.98E+05	2.48E-02	6.21E-06	6.30E-03	3.87E-03	9.44E-05	25	714.15	979	16455	2.1E-06	0.0E+00	S	X	
309002 Aldrin	2.45E+06	1.32E-02	4.86E-06	1.70E-02	6.95E-03	1.70E-04	25	603.01	839.37	15000	4.9E-03	1.1E-04	S		X
319846 alpha-HCH (alpha-BHC)	1.23E+03	1.42E-02	7.34E-06	2.00E+00	4.34E-04	1.06E-05	25	596.55	839.36	15000	1.8E-03	0.0E+00	S		
541731 1,3-Dichlorobenzene	1.98E+03	6.92E-02	7.86E-06	1.34E+02	1.27E-01	3.09E-03	25	446	684	9230.18	0.0E+00	1.1E-01	L		X
542756 1,3-Dichloropropene	4.57E+01	6.26E-02	1.00E-05	2.80E+03	7.24E-01	1.77E-02	25	381.15	587.38	7900	4.0E-06	2.0E-02	L		
630206 1,1,1,2-Tetrachloroethane	1.16E+02	7.10E-02	7.90E-06	1.10E+03	9.90E-02	2.41E-03	25	403.5	624	9768.282525	7.4E-06	1.1E-01	L		X
1634044 MTBE	7.26E+00	1.02E-01	1.05E-05	5.10E+04	2.56E-02	6.23E-04	25	328.3	497.1	6677.66	0.0E+00	3.0E+00	L		
7439976 Mercury (elemental)	5.20E+01	3.07E-02	6.30E-06	2.00E+01	4.40E-01	1.07E-02	25	629.88	1750	14127	0.0E+00	3.0E-04	L		

ProUCL Output

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

Units = ug/kg

From File WorkSheet.wst
 Full Precision OFF
 Confidence Coefficient 95%
 Number of Bootstrap Operations 2000

Benzene

General Statistics

Number of Valid Data	134	Number of Detected Data	2
Number of Distinct Detected Data	2	Number of Non-Detect Data	132
Number of Missing Values	21	Percent Non-Detects	98.51%

Raw Statistics

Minimum Detected	1.2
Maximum Detected	3800
Mean of Detected	1901
SD of Detected	2686
Minimum Non-Detect	5.2
Maximum Non-Detect	7000

Log-transformed Statistics

Minimum Detected	0.182
Maximum Detected	8.243
Mean of Detected	4.213
SD of Detected	5.7
Minimum Non-Detect	1.649
Maximum Non-Detect	8.854

Note: Data have multiple DLs - Use of KM Method is recommended
 For all methods (except KM, DL/2, and ROS Methods),
 Observations < Largest ND are treated as NDs

Number treated as Non-Detect	134
Number treated as Detected	0
Single DL Non-Detect Percentage	100.00%

Warning: Data set has only 2 Distinct Detected Values.

This may not be adequate enough to compute meaningful and reliable test statistics and estimates.

The Project Team may decide to use alternative site specific values to estimate environmental parameters (e.g., EPC, BTV).

Unless Data Quality Objectives (DQOs) have been met, it is suggested to collect additional observations.

ProUCL Output

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.
Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.
However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

Normal Distribution Test with Detected Values Only		UCL Statistics	Lognormal Distribution Test with Detected Values Only	
Shapiro Wilk Test Statistic		N/A	Shapiro Wilk Test Statistic	N/A
5% Shapiro Wilk Critical Value		N/A	5% Shapiro Wilk Critical Value	N/A
Data not Normal at 5% Significance Level			Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution			Assuming Lognormal Distribution	
DL/2 Substitution Method			DL/2 Substitution Method	
Mean	57.21		Mean	1.126
SD	444.3		SD	0.878
95% DL/2 (t) UCL	120.8		95% H-Stat (DL/2) UCL	5.312
Maximum Likelihood Estimate(MLE) Method	N/A		Log ROS Method	
MLE method failed to converge properly			Mean in Log Scale	N/A
			SD in Log Scale	N/A
			Mean in Original Scale	N/A
			SD in Original Scale	N/A
			95% t UCL	N/A
			95% Percentile Bootstrap UCL	N/A
			95% BCA Bootstrap UCL	N/A
			95% H-UCL	N/A
Gamma Distribution Test with Detected Values Only			Data Distribution Test with Detected Values Only	

ProUCL Output

	k star (bias corrected)	N/A	Data do not follow a Discernable Distribution (0.05)
	Theta Star	N/A	
	nu star	N/A	
	A-D Test Statistic	N/A	Nonparametric Statistics
	5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method
	K-S Test Statistic	N/A	Mean
	5% K-S Critical Value	N/A	SD
			SE of Mean
			95% KM (t) UCL
			95% KM (z) UCL
			95% KM (jackknife) UCL
			95% KM (bootstrap t) UCL
			95% KM (BCA) UCL
			95% KM (Percentile Bootstrap) UCL
			95% KM (Chebyshev) UCL
			97.5% KM (Chebyshev) UCL
			99% KM (Chebyshev) UCL
			Potential UCLs to Use
			97.5% KM (Chebyshev) UCL
			281.1

Data not Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

	Gamma ROS Statistics using Extrapolated Data		
	Minimum	N/A	
	Maximum	N/A	
	Mean	N/A	
	Median	N/A	
	SD	N/A	
	k star	N/A	
	Theta star	N/A	
	Nu star	N/A	
	AppChi2	N/A	
	95% Gamma Approximate UCL (Use when n >= 40)	N/A	
	95% Adjusted Gamma UCL (Use when n < 40)	N/A	

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.

Ethylbenzene

ProUCL Output

General Statistics			
Number of Valid Data	134	Number of Detected Data	3
Number of Distinct Detected Data	3	Number of Non-Detect Data	131
Number of Missing Values	21	Percent Non-Detects	97.76%

Raw Statistics

Minimum Detected	1.3
Maximum Detected	54000
Mean of Detected	19300
SD of Detected	30114
Minimum Non-Detect	5.2
Maximum Non-Detect	6

Log-transformed Statistics

Minimum Detected	0.262
Maximum Detected	10.9
Mean of Detected	6.476
SD of Detected	5.539
Minimum Non-Detect	1.649
Maximum Non-Detect	1.792

Note: Data have multiple DLs - Use of KM Method is recommended
 For all methods (except KM, DL/2, and ROS Methods),
 Observations < Largest ND are treated as NDs

Number treated as Non-Detect	132
Number treated as Detected	2
Single DL Non-Detect Percentage	98.51%

Warning: There are only 3 Distinct Detected Values in this data set
The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.
Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.
 However, results obtained using 4 to 9 distinct values may not be reliable.
 It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	
Shapiro Wilk Test Statistic	0.804	Shapiro Wilk Test Statistic	0.921
5% Shapiro Wilk Critical Value	0.767	5% Shapiro Wilk Critical Value	0.767
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	

ProUCL Output

Assuming Normal Distribution

DL/2 Substitution Method	
Mean	434.8
SD	4674
95% DL/2 (t) UCL	1104
Maximum Likelihood Estimate(MLE) Method	N/A
MLE method failed to converge properly	

Assuming Lognormal Distribution

DL/2 Substitution Method	
Mean	1.147
SD	1.057
95% H-Stat (DL/2) UCL	6.764
Log ROS Method	
Mean in Log Scale	0.274
SD in Log Scale	3.435
Mean in Original Scale	481
SD in Original Scale	4674
95% t UCL	1150
95% Percentile Bootstrap UCL	1282
95% BCA Bootstrap UCL	2069
95% H-UCL	2189

Gamma Distribution Test with Detected Values Only

k star (bias corrected)	N/A
Theta Star	N/A
nu star	N/A

A-D Test Statistic	N/A
5% A-D Critical Value	N/A
K-S Test Statistic	N/A
5% K-S Critical Value	N/A

Data not Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

Gamma ROS Statistics using Extrapolated Data	
Minimum	N/A
Maximum	N/A
Mean	N/A

Data Distribution Test with Detected Values Only

Data appear Normal at 5% Significance Level

Nonparametric Statistics

Kaplan-Meier (KM) Method	
Mean	433.4
SD	4657
SE of Mean	492.7
95% KM (t) UCL	1249
95% KM (z) UCL	1244
95% KM (jackknife) UCL	2976
95% KM (bootstrap t) UCL	4468
95% KM (BCA) UCL	54000
95% KM (Percentile Bootstrap) UCL	54000

ProUCL Output

Median	N/A	95% KM (Chebyshev) UCL	2581
SD	N/A	97.5% KM (Chebyshev) UCL	3510
k star	N/A	99% KM (Chebyshev) UCL	5336
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	1249
95% Gamma Approximate UCL (Use when n >= 40)	N/A	95% KM (Percentile Bootstrap) UCL	54000
95% Adjusted Gamma UCL (Use when n < 40)	N/A		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.

Tetrachloroethene

General Statistics			
Number of Valid Data	134	Number of Detected Data	1
Number of Distinct Detected Data	1	Number of Non-Detect Data	133
Number of Missing Values	21	Percent Non-Detects	99.25%

Warning: Only one distinct data value was detected! ProUCL (or any other software) should not be used on such a data set!

It is suggested to use alternative site specific values determined by the Project Team to estimate environmental parameters (e.g., EPC, BTV).

The data set for variable Tetrachloroethene was not processed!

Toluene

General Statistics

ProUCL Output

Number of Valid Data	134	Number of Detected Data	29
Number of Distinct Detected Data	24	Number of Non-Detect Data	105
Number of Missing Values	21	Percent Non-Detects	78.36%

Raw Statistics

Minimum Detected	1.2
Maximum Detected	82000
Mean of Detected	3315
SD of Detected	15355
Minimum Non-Detect	5.3
Maximum Non-Detect	54

Log-transformed Statistics

Minimum Detected	0.182
Maximum Detected	11.31
Mean of Detected	1.905
SD of Detected	2.494
Minimum Non-Detect	1.668
Maximum Non-Detect	3.989

Note: Data have multiple DLs - Use of KM Method is recommended
 For all methods (except KM, DL/2, and ROS Methods),
 Observations < Largest ND are treated as NDs

Number treated as Non-Detect	132
Number treated as Detected	2
Single DL Non-Detect Percentage	98.51%

UCL Statistics

Normal Distribution Test with Detected Values Only

Shapiro Wilk Test Statistic	0.235
5% Shapiro Wilk Critical Value	0.926

Data not Normal at 5% Significance Level

Lognormal Distribution Test with Detected Values Only

Shapiro Wilk Test Statistic	0.577
5% Shapiro Wilk Critical Value	0.926

Data not Lognormal at 5% Significance Level

Assuming Normal Distribution

DL/2 Substitution Method	
Mean	719.8
SD	7177
95% DL/2 (t) UCL	1747

Assuming Lognormal Distribution

DL/2 Substitution Method	
Mean	1.232
SD	1.214
95% H-Stat (DL/2) UCL	9.227

Maximum Likelihood Estimate(MLE) Method N/A

MLE method failed to converge properly

Log ROS Method	
Mean in Log Scale	1.09
SD in Log Scale	1.565
Mean in Original Scale	720.6

ProUCL Output

SD in Original Scale	7177
95% t UCL	1748
95% Percentile Bootstrap UCL	1944
95% BCA Bootstrap UCL	3063
95% H-UCL	14.75

Gamma Distribution Test with Detected Values Only

k star (bias corrected)	0.137
Theta Star	24238
nu star	7.932

A-D Test Statistic	8.584
5% A-D Critical Value	0.934
K-S Test Statistic	0.934
5% K-S Critical Value	0.183

Data not Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

Gamma ROS Statistics using Extrapolated Data

Minimum	0.000001
Maximum	82000
Mean	1025
Median	0.000001
SD	7221
k star	0.0629
Theta star	16302
Nu star	16.85
AppChi2	8.564

95% Gamma Approximate UCL (Use when n >= 40)	2016
95% Adjusted Gamma UCL (Use when n < 40)	2032

Note: DL/2 is not a recommended method.

Data Distribution Test with Detected Values Only

Data do not follow a Discernable Distribution (0.05)

Nonparametric Statistics

Kaplan-Meier (KM) Method

Mean	719.4
SD	7150
SE of Mean	628.6
95% KM (t) UCL	1761
95% KM (z) UCL	1753
95% KM (jackknife) UCL	1746
95% KM (bootstrap t) UCL	1623792
95% KM (BCA) UCL	1944
95% KM (Percentile Bootstrap) UCL	1943
95% KM (Chebyshev) UCL	3459
97.5% KM (Chebyshev) UCL	4645
99% KM (Chebyshev) UCL	6974

Potential UCLs to Use

97.5% KM (Chebyshev) UCL	4645
--------------------------	------

ProUCL Output

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.

Xylenes (total)

General Statistics			
Number of Valid Data	134	Number of Detected Data	8
Number of Distinct Detected Data	7	Number of Non-Detect Data	126
Number of Missing Values	21	Percent Non-Detects	94.03%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	1.5	Minimum Detected	0.405
Maximum Detected	260000	Maximum Detected	12.47
Mean of Detected	36628	Mean of Detected	3.755
SD of Detected	90991	SD of Detected	4.823
Minimum Non-Detect	5.2	Minimum Non-Detect	1.649
Maximum Non-Detect	6	Maximum Non-Detect	1.792

**Note: Data have multiple DLs - Use of KM Method is recommended
For all methods (except KM, DL/2, and ROS Methods),
Observations < Largest ND are treated as NDs**

Number treated as Non-Detect	131
Number treated as Detected	3
Single DL Non-Detect Percentage	97.76%

**Warning: There are only 8 Detected Values in this data
Note: It should be noted that even though bootstrap may be performed on this data set
the resulting calculations may not be reliable enough to draw conclusions**

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

ProUCL Output

Normal Distribution Test with Detected Values Only

Shapiro Wilk Test Statistic	0.486
5% Shapiro Wilk Critical Value	0.818

Data not Normal at 5% Significance Level

Assuming Normal Distribution

DL/2 Substitution Method	
Mean	2189
SD	22619
95% DL/2 (t) UCL	5426

Maximum Likelihood Estimate(MLE) Method N/A

MLE yields a negative mean

Lognormal Distribution Test with Detected Values Only

Shapiro Wilk Test Statistic	0.713
5% Shapiro Wilk Critical Value	0.818

Data not Lognormal at 5% Significance Level

Assuming Lognormal Distribution

DL/2 Substitution Method	
Mean	1.19
SD	1.283
95% H-Stat (DL/2) UCL	9.845

Log ROS Method

Mean in Log Scale 0.85

SD in Log Scale 2.556

Mean in Original Scale 2200

SD in Original Scale 22618

95% t UCL 5436

95% Percentile Bootstrap UCL 6078

95% BCA Bootstrap UCL 8512

95% H-UCL 147.5

Gamma Distribution Test with Detected Values Only

k star (bias corrected)	0.157
Theta Star	233428
nu star	2.511

A-D Test Statistic 1.381

5% A-D Critical Value 0.866

K-S Test Statistic 0.866

5% K-S Critical Value 0.328

Data not Gamma Distributed at 5% Significance Level

Data Distribution Test with Detected Values Only

Data do not follow a Discernable Distribution (0.05)

Nonparametric Statistics

Kaplan-Meier (KM) Method

Mean 2189

SD 22535

SE of Mean 2081

95% KM (t) UCL 5636

ProUCL Output

Assuming Gamma Distribution			95% KM (z) UCL	5612
Gamma ROS Statistics using Extrapolated Data			95% KM (jackknife) UCL	5425
Minimum	0.000001		95% KM (bootstrap t) UCL	15633168
Maximum	260000		95% KM (BCA) UCL	6070
Mean	7625		95% KM (Percentile Bootstrap) UCL	6069
Median	0.000001		95% KM (Chebyshev) UCL	11260
SD	25532		97.5% KM (Chebyshev) UCL	15185
k star	0.0587		99% KM (Chebyshev) UCL	22896
Theta star	129895			
Nu star	15.73			
AppChi2	7.774			
95% Gamma Approximate UCL (Use when n >= 40)	15432			
95% Adjusted Gamma UCL (Use when n < 40)	15554			

Potential UCLs to Use

97.5% KM (Chebyshev) UCL 15185

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.

ProUCL Output

ProUCL Output

ProUCL Input Table

Location	Sample Number	Depth (ft bgs)	Laboratory Sample Number	Sample Date	Benzene	d_Benzene	Ethylbenzene	d_Ethylbenzene	Tetrachloroethene	d_Tetrachloroethene	Toluene	d_Toluene	Xylenes (total)	d_Xylenes (total)
1271	CAN127-1271-0000	0	0313740003SA	9/23/1993	5.8	0	5.8	0	5.8	0	5.8	0	5.8	0
1271	CAN127-1271-0002	2	0313740004SA	9/23/1993	5.8	0	5.8	0	5.8	0	5.8	0	5.8	0
1271	CAN127-1271-0004	4	0313740005SA	9/23/1993	5.8	0	5.8	0	5.8	0	5.8	0	5.8	0
1271	CAN127-1271-0008	8	0313740006SA	9/23/1993	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
1272	CAN127-1272-0000	0	0313740007SA	9/23/1993	5.8	0	5.8	0	5.8	0	5.8	0	5.8	0
1272	CAN127-1272-0002	2	0313740008SA	9/23/1993	6.0	0	6.0	0	6.0	0	6.0	0	6.0	0
1272	CAN127-1272-0004	4	0313740009SA	9/23/1993	5.9	0	5.9	0	5.9	0	5.9	0	5.9	0
1272	CAN127-1272-0008	8	0313740010SA	9/23/1993	5.9	0	5.9	0	5.9	0	5.9	0	5.9	0
1273	CAN127-1273-0000	0	0312160001SA	9/13/1993	5.2	0	5.2	0	5.2	0	12	1	3.4	1
1273	CAN127-1273-0002	2	0312160002SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0004	4	0312160004SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0008	8	0312160003SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0018	18	0312160005SA	9/13/1993	5.6	0	5.6	0	5.6	0	3.5	1	5.6	0
1273	CAN127-1273-0028	28	0312160006SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0038	38	0312160007SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0048	48	0312160008SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1273	CAN127-1273-0058	58	0312160009SA	9/13/1993	5.4	0	5.4	0	5.4	0	1.2	1	5.4	0
1274	CAN127-1274-0000	0	0312770001SA	9/14/1993	5.5	0	5.5	0	5.5	0	2.3	1	1.5	1
1274	CAN127-1274-0002	2	0312770002SA	9/14/1993	5.5	0	5.5	0	5.5	0	2.8	1	5.5	0
1274	CAN127-1274-0004	4	0312770003SA	9/14/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1274	CAN127-1274-0008	8	0312770004SA	9/14/1993	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
1274	CAN127-1274-0018	18	0312770005SA	9/14/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1274	CAN127-1274-0028	28	0312770007SA	9/14/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1274	CAN127-1274-0038	38	0312770008SA	9/14/1993	5.6	0	5.6	0	5.6	0	2.0	1	5.6	0
1274	CAN127-1274-0048	48	0312770009SA	9/14/1993	5.5	0	5.5	0	5.5	0	3.3	1	5.5	0
1274	CAN127-1274-0058	58	0312770010SA	9/14/1993	5.4	0	5.4	0	5.4	0	1.6	1	5.4	0
1275	CAN127-1275-0000	0	0312770011SA	9/14/1993	5.2	0	5.2	0	5.2	0	5.2	1	5.2	0
1275	CAN127-1275-0002	2	0312770012SA	9/14/1993	5.8	0	5.8	0	5.8	0	5.8	0	5.8	0
1275	CAN127-1275-0004	4	0312770013SA	9/14/1993	5.7	0	5.7	0	5.7	0	5.4	1	5.7	0
1275	CAN127-1275-0008	8	0312770014SA	9/14/1993	5.8	0	5.8	0	5.8	0	18	1	5.8	0
1275	CAN127-1275-0018	18	0312770015SA	9/14/1993	1.2	1	1.3	1	2.9	1	6.2	1	2.4	1
1275	CAN127-1275-0028	28	0312770016SA	9/14/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1275	CAN127-1275-0038	38	0312770017SA	9/14/1993	5.5	0	5.5	0	5.5	0	7.2	1	5.5	0
1275	CAN127-1275-0048	48	0312770018SA	9/14/1993	5.6	0	5.6	0	5.6	0	12	1	5.6	0
1275	CAN127-1275-0058	58	0312770019SA	9/14/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1276	CAN127-1276-0000	0	0312160012SA	9/13/1993	5.2	0	5.2	0	5.2	0	15	1	12	1
1276	CAN127-1276-0002	2	0312160013SA	9/13/1993	5.4	0	5.4	0	5.4	0	5.4	0	5.4	0
1276	CAN127-1276-0004	4	0312150009SA	9/13/1993	5.4	0	5.4	0	5.4	0	5.4	0	5.4	0
1276	CAN127-1276-0008	8	0312150010SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1276	CAN127-1276-0018	18	0312150011SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1276	CAN127-1276-0028	28	0312150012SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1276	CAN127-1276-0038	38	0312150013SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1276	CAN127-1276-0048	48	0312150014SA	9/13/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1276	CAN127-1276-0058	58	0312150015SA	9/13/1993	5.4	0	5.4	0	5.4	0	2.5	1	5.4	0

ProUCL Input Table

Location	Sample Number	Depth (ft bgs)	Laboratory Sample Number	Sample Date	Benzene	d_Benzene	Ethylbenzene	d_Ethylbenzene	Tetrachloroethene	d_Tetrachloroethene	Toluene	d_Toluene	Xylenes (total)	d_Xylenes (total)
1277	CAN127-1277-0000	0	0311840009SA	9/12/1993	5.3	0	5.3	0	5.3	0	5.5	1	5.9	1
1277	CAN127-1277-0002	2	0311840010SA	9/12/1993	5.4	0	5.4	0	5.4	0	3.8	1	1.5	1
1277	CAN127-1277-0004	4	0311840011SA	9/12/1993	5.5	0	5.5	0	5.5	0	2.1	1	5.5	0
1277	CAN127-1277-0008	8	0311840012SA	9/12/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1277	CAN127-1277-0018	18	0311840013SA	9/12/1993	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
1277	CAN127-1277-0028	28	0311840014SA	9/12/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1277	CAN127-1277-0038	38	0311840015SA	9/12/1993	5.5	0	5.5	0	5.5	0	1.7	1	5.5	0
1277	CAN127-1277-0048	48	0311840016SA	9/12/1993	5.5	0	5.5	0	5.5	0	2.0	1	5.5	0
1277	CAN127-1277-0058	58	0311840017SA	9/12/1993	5.5	0	5.5	0	5.5	0	2.6	1	5.5	0
1278	CAN127-1278-0000	0	0311840001SA	9/12/1993	5.3	0	5.3	0	5.3	0	5.3	0	5.3	0
1278	CAN127-1278-0002	2	0311840002SA	9/12/1993	5.4	0	5.4	0	5.4	0	5.4	0	5.4	0
1278	CAN127-1278-0004	4	0311840004SA	9/12/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1278	CAN127-1278-0008	8	0311840005SA	9/12/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1278	CAN127-1278-0018	18	0311840006SA	9/12/1993	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
1278	CAN127-1278-0028	28	0311840007SA	9/12/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1278	CAN127-1278-0038	38	0311840008SA	9/12/1993	5.5	0	5.5	0	5.5	0	5.5	0	5.5	0
1278	CAN127-1278-0048	48	0312160010SA	9/13/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
1278	CAN127-1278-0058	58	0312160011SA	9/13/1993	5.6	0	5.6	0	5.6	0	5.6	0	5.6	0
2709	CAN127-2709-0000	0	0398710011SA	12/13/1994	7000	0	3900	1	5.7	0	14000	1	33000	1
2709	CAN127-2709-0005	5	0398710009SA	12/13/1994	5.8	0	5.8	0	5.7	0	5.8	0	5.8	0
2709	CAN127-2709-0010	10	0398710008SA	12/13/1994	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
2710	CAN127-2710-0000	0	0398710005SA	12/13/1994	3800	1	54000	1	5.7	0	82000	1	260000	1
2710	CAN127-2710-0005	5	0398710003SA	12/13/1994	5.9	0	5.9	0	5.7	0	5.9	0	5.9	0
2710	CAN127-2710-0010	10	0398710007SA	12/13/1994	5.5	0	5.5	0	5.7	0	5.5	0	5.5	0
2711	CAN127-2711-0000	0	0397370007SA	12/9/1994	5.4	0	5.4	0	5.7	0	5.4	0	5.4	0
2711	CAN127-2711-0005	5	0397370008SA	12/9/1994	5.3	0	5.3	0	5.7	0	5.3	0	5.3	0
2711	CAN127-2711-0010	10	0397370009SA	12/9/1994	5.7	0	5.7	0	5.7	0	5.7	0	5.7	0
2711	CAN127-2711-0015	15	0397370010SA	12/9/1994	5.5	0	5.5	0	5.7	0	5.5	0	5.5	0
2711	CAN127-2711-0020	20	0397370011SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2711	CAN127-2711-0025	25	0397370012SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2711	CAN127-2711-0030	30	0397370013SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2711	CAN127-2711-0035	35	0397740013SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2711	CAN127-2711-0040	40	0397740014SA	12/9/1994	5.5	0	5.5	0	5.7	0	5.5	0	5.5	0
2711	CAN127-2711-0050	50	0397740015SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2711	CAN127-2711-0060	60	0397740016SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2712	CAN127-2712-0000	0	0397130001SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2712	CAN127-2712-0005	5	0397130002SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2712	CAN127-2712-0010	10	0397130003SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2712	CAN127-2712-0015	15	0397130004SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2712	CAN127-2712-0020	20	0397130005SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2712	CAN127-2712-0025	25	0397130006SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2712	CAN127-2712-0030	30	0397130007SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2712	CAN127-2712-0035	35	0397130008SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.8	0	5.6	0
2712	CAN127-2712-0040	40	0397130009SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0

ProUCL Input Table

Location	Sample Number	Depth (ft bgs)	Laboratory Sample Number	Sample Date	Benzene	d_Benzene	Ethylbenzene	d_Ethylbenzene	Tetrachloroethene	d_Tetrachloroethene	Toluene	d_Toluene	Xylenes (total)	d_Xylenes (total)
2712	CAN127-2712-0050	50	0397130010SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2712	CAN127-2712-0060	60	0397130011SA	12/8/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2713	CAN127-2713-0000	0	0397380001SA	12/9/1994	5.6	0	5.6	0	5.7	0	1.3	1	5.6	0
2713	CAN127-2713-0005	5	0397380002SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2713	CAN127-2713-0010	10	397380003SA	12/9/1994	5.6	0	5.6	0	5.7	0	1.2	1	5.6	0
2713	CAN127-2713-0015	15	039780004SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.7	0	5.6	0
2713	CAN127-2713-0020	20	039738005SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2713	CAN127-2713-0025	25	039738006SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.8	0	5.6	0
2713	CAN127-2713-0030	30	0397380007SA	12/9/1994	5.6	0	5.6	0	5.7	0	1.6	1	5.6	0
2713	CAN127-2713-0035	35	0397380008SA	12/9/1994	5.6	0	5.6	0	5.7	0	9.0	1	5.6	0
2713	CAN127-2713-0040	40	0397380009SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2713	CAN127-2713-0050	50	0397380010SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.7	0	5.6	0
2713	CAN127-2713-0060	60	0397380011SA	12/9/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2714	CAN127-2714-0000	0	0396880006SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2714	CAN127-2714-0005	5	0396880008SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2714	CAN127-2714-0010	10	0396880009SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2714	CAN127-2714-0015	15	0396880010SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2714	CAN127-2714-0020	20	0396880011SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2714	CAN127-2714-0025	25	0396880012SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2714	CAN127-2714-0030	30	0396880013SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2714	CAN127-2714-0035	35	0396880014SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2714	CAN127-2714-0040	40	0396880015SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2714	CAN127-2714-0050	50	0396880016SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2714	CAN127-2714-0060	60	0396880017SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2715	CAN127-2715-0000	0	0396860001SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2715	CAN127-2715-0005	5	0396860002SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.3	0	5.6	0
2715	CAN127-2715-0010	10	0396860003SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2715	CAN127-2715-0015	15	0396860004SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0
2715	CAN127-2715-0020	20	0396860005SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2715	CAN127-2715-0025	25	0396860006SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2715	CAN127-2715-0030	30	0396860007SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2715	CAN127-2715-0035	35	0396860008SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2715	CAN127-2715-0040	40	039680009SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2715	CAN127-2715-0050	50	0396860010SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2715	CAN127-2715-0060	60	0397130012SA	12/7/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2716	CAN127-2716-0000	0	0396550007SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2716	CAN127-2716-0005	5	0396550008SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.8	0	5.6	0
2716	CAN127-2716-0010	10	0396550009SA	12/6/1994	5.6	0	5.6	0	5.7	0	2.8	1	5.6	0
2716	CAN127-2716-0015	15	0396550010SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2716	CAN127-2716-0020	20	0396550011SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2716	CAN127-2716-0025	25	0396550012SA	12/6/1994	5.6	0	5.6	0	5.7	0	6.4	0	5.6	0
2716	CAN127-2716-0030	30	0396550013SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2716	CAN127-2716-0035	35	0396550003SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.6	0	5.6	0
2716	CAN127-2716-0040	40	0396550004SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.4	0	5.6	0

ProUCL Input Table

Location	Sample Number	Depth (ft bgs)	Laboratory Sample Number	Sample Date	Benzene	d_Benzene	Ethylbenzene	d_Ethylbenzene	Tetrachloroethene	d_Tetrachloroethene	Toluene	d_Toluene	Xylenes (total)	d_Xylenes (total)
2716	CAN127-2716-0050	50	0396550005SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
2716	CAN127-2716-0060	60	0396550006SA	12/6/1994	5.6	0	5.6	0	5.7	0	5.5	0	5.6	0
127SB01	127SB0100	0 to 3	B141-01	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB02	127SB0200	0 to 2.5	B141-02	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB03	127SB0300	0 to 2.5	B141-03	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB04	127SB0400	0 to 2.5	B141-04	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB05	127SB0500	0 to 3	B141-05	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB06	127SB0600	0 to 3	B141-06	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB07	127SB0700	0 to 3	B141-07	2/13/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB08	127SB0800	0 to 3	B175-01	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB09	127SB0900	0 to 3	B175-02	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB10	127SB1000	0 to 3	B175-03	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB11	127SB1100	0 to 3	B175-04	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB12	127SB1200	0 to 3	B175-05	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB13	127SB1300	0 to 3	B175-06	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB13M	127SB1300M	0 to 3	B175-07	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB13D	127SB1300D	0 to 3	B175-08	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB14	127SB1400	0 to 3	B175-09	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB15	127SB1500	0 to 3	B175-10	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB16	127SB1600	0 to 3	B175-11	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB17	127SB1700	0 to 3	B175-12	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB18	127SB1800	0 to 3	B175-13	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1
127SB1810	127SB1810	0 to 3	B175-14	2/14/2008	1E+31	1	1E+31	1	1E+31	1	1E+31	1	1E+31	1